

High Precision CC/CV Primary-Side Controller

General Description

The PN8232 is a high precision CC/CV primary side controller, specifically designed for a high performance low power AC/DC charger and LED lighting with minimal external components. PN8232 operates in primary-side sensing and regulation, so opto-coupler and TL431 could be eliminated. PN8232 offers complete protection coverage with automatic self-recovery feature including Cycle-by-Cycle current limiting protection (OCP), over voltage protection (OVP) and feedback loop open protection (OLP), over temperature protection (OTP) and short circuit protection etc. In CC control, the current and output power setting can be adjusted externally by the sense resistor R_{cs} at CS pin. In CV control, PFM operations are utilized to achieve high performance and high efficiency. In addition, good load regulation is achieved by the built-in cable drop compensation.


Features

- $\pm 5\%$ Constant current Regulation at Universal AC input
- Primary-side Sensing and Regulation Without TL431 and Opt coupler
- Programmable CV and CC Regulation
- Programmable Cable Drop Compensation
- Built-in Primary winding inductance compensation
- Audio Noise Free
- Excellent Protection Coverage:
 - ◇ Over Temperature Protection (OTP)
 - ◇ VDD Under Voltage Lockout (UVLO)
 - ◇ Cycle-by-Cycle Current Limiting (OCP)
 - ◇ Open Loop Protection (OLP)
 - ◇ VDD Over Voltage Protection (OVP)
 - ◇ Auto-recovery protection Mode

Applications

- Switch AC/DC Adaptor and Battery Charger
- STB Power Supply
- LED Lighting

Package/Order Information



Order codes	Package	V _{cable}	Typical power
			85~265 V _{AC}
PN8232TCC-R1	SOT23-6	3%	36W

Typical Application

